



34935 Flyover Ct. Bakersfield, CA 93308  
Phone: (661) 588-8085 | Fax: (661) 588-8295

**INSTALL INSTRUCTIONS:**

**Cognito High Clearance  
Lower Radius Rod Kit for  
Polaris  
SKU: 360-90794**



**PARTS LIST FOR SKU: 360-90794**

| QUANTITY | PART #              | DESCRIPTION                      |
|----------|---------------------|----------------------------------|
| 2        | 8712                | Radius Rod Bar                   |
| 4        | UNI-BALL-WSSX12T-F1 | 3/4" Spherical Bearing (Uniball) |
| 4        | HARDWARE-IRR-1 3/8" | Retaining Ring                   |
| 8        | 6292                | Spacer Adapter                   |
| 2        | 6679                | RADIUS ROD BUSHING               |

**WARNING**

Please read this entire instruction sheet before beginning installation. Proper installation of these components requires a qualified mechanic. Always wear safety glasses when using power tools, and take appropriate precautions when working under a vehicle. If these instructions are not properly followed you may jeopardize your, and your passenger's safety, and severe frame, suspension or tire damage may also result from improper installation.

**INTRODUCTION**

- The OEM Polaris radius rods, under heavy duty use, are prone to bending and wearing out the bearings in the ends which become very sloppy. A bent or broken radius rod can cause much more damage, sometimes breaking or bending rear axles, rear cv joints, trailing arms, rear shock shafts, and sway bar end links.
- Please note, it is highly recommended to use the Cognito Radius Rod Cage in place of the stock radius rod plate.
- This is a fixed length radius rod kit, no need for adjustability on the lower radius rods. Fixed aids in quicker and easier installation so no length needs to be setup.

**REQUIREMENTS**

- Installation requires a qualified mechanic.
- Read instructions carefully and study the pictures (if included) before attempting installation.
- Check the parts and hardware packages against the parts list to assure that your kit is complete.
- Always wear safety glasses when using power tools.

## INSTALLATION

1. All fasteners will be re-used, so retain all removed hardware for re-use.
2. Raise the rear of your RZR up and support by the frame so that the suspension droops out and tires are off the ground. Remove rear tires.
3. Remove the fasteners holding the outer ends of the stock lower radius rods to the spindle bearing carriers, and the inner ends from the chassis and sandwich plate.
4. Now install the lower radius rod assemblies in place of the OEM lower radius rods, using a spacer adapter on each side of each rod end. Insert the radius rod bushings around the spacer adapters between the radius rod and the chassis. Tighten fasteners to 75 ft.-lbs.
5. Install rear wheels and tighten lug nuts to OEM spec which is 120 ft lbs.

## WARRANTY / RETURN POLICY / SAFETY

### **Cognito Limited Lifetime Warranty**

Cognito Motorsports, Inc. hereinafter “Cognito,” warrants to the original retail purchaser, that its suspension products are free from workmanship and material defects for as long as the purchaser owns the vehicle on which the product(s) were originally installed. This warranty will be void if any modifications are made to the components, including alterations to the surface finish, i.e.; painting, powder coating, plating, and/or welding, or if they are improperly installed. Cognito truck suspension products are not designed nor intended to be installed on “competition” vehicles used in race applications, stunt or for exhibition purposes that are outside of the intended operating conditions specified by the manufacturer. Racing and competition are defined as any contests between two or more vehicles; or vehicles competing individually on off road circuits in timed events (whether or not such contests are for an award or prize).

This warranty does not include coverage for police, taxi, government or commercial vehicles, and the warranty does not cover Cognito products sold outside of the USA. Cognito’s obligations under this warranty are specified and applied at its sole discretion, and warranty coverage is limited to repair or replacement of the defective product(s). Any and all costs of removal, installation or reinstallation; freight charges, incidental or consequential damages associated with the covered products are expressly excluded from this warranty.

The following items are exempt from Cognito limited warranty coverage: bushings, bump stops, tie-rod ends (Heim joints) and limiting straps. These parts are “consumables” and designed to wear as a normal part of their duty cycle, therefore they are not considered defective when worn. The aforementioned products are warrantied separately against defects in workmanship, for 60 days from the date of purchase. As a condition of warranty validation, respective Cognito suspension components must be installed as a complete system (not combined with non-Cognito hardware or ancillary parts). Any substitutions or omission of required components will void the warranty. Some minor cosmetic wear and imperfections may occur to parts during shipping, which is not covered under this warranty. This limited warranty does not apply to any components that have been subjected to collision damage, negligence, alteration, abuse, or misuse, and coverage does not extend to products manufactured by third-party companies. Cognito reserves the right to supersede, discontinue, or change the design, finish, part number and/or application of its parts when deemed necessary, without notice.

### **Return Policy**

Product returns will not be accepted without prior written approval from an authorized Cognito representative. All products being returned must be shipped via trackable, prepaid freight. Returned products are subject to a 25% percent restocking fee. The eligible return period for products purchased directly from Cognito is 30 days from the verified date when the product(s) were originally received by the purchaser.

### **Product Safety Advisory**

The installation of Cognito steering and suspension components will modify your vehicle’s original factory equipment and geometry, which may cause it to handle differently than a stock (unaltered) vehicle. Installation of these components is not intended to strengthen nor reinforce the vehicle’s frame, nor are they designed to increase rollover protection. It is necessary to periodically inspect all suspension and drive train components for proper attachment, torque specifications, operation, and for any potential unusual wear or damage. Installation of these parts will modify the height of the vehicle and may raise the center of gravity. Modifying vehicle height combined with off road operation may increase your vehicle’s susceptibility to rollover conditions, which may cause serious injury or death. Many states regulate allowable vehicle height modifications, and it is your responsibility to know and comply with the legal requirements specified by the laws where you reside. Modifications to your vehicle’s ride height may also affect the ride quality, driver input response, trackability and handling, and wear to your vehicle’s suspension components and tires.